

ICC-ES SAVE: Verification of Attributes Report™**VAR-1018**

Issued April 1, 2011

This report is subject to renewal in one year.www.icc-es.org/save | 1-800-423-6587 | (562) 699-0543 A Subsidiary of the International Code Council®**DIVISION: 04 00 00—MASONRY**
Section: 04 22 00—Concrete Unit Masonry**REPORT HOLDER:****ANGELUS BLOCK COMPANY, INC.**
11374 TUXFORD STREET
SUN VALLEY, CALIFORNIA 91352
(818) 767-8576
www.angelusblock.com
info@angelusblock.com**EVALUATION SUBJECT:****ANGELUS BLOCK CONCRETE MASONRY UNITS****1.0 EVALUATION SCOPE****Compliance with the following evaluation guideline:**

ICC-ES Evaluation Guideline for Determination of Recycled Content of Materials (EG101), dated October 1, 2008 (editorially revised July 2009).

Compliance eligibility with the applicable sections of the following green building rating systems, standards and codes:

- 2010 California Green Building Standards Code (CALGreen), Title 24, Part 11 (See Table 2 for details)
- National Green Building Standard (ICC 700-2008) (See Table 3 for details)
- LEED 2009 for New Construction and Major Renovations (See Table 4 for details)
- LEED 2009 for Schools New Construction and Major Renovations (See Table 5 for details)
- LEED 2009 for Core and Shell Development (See Table 6 for details)
- LEED for Homes 2008 (See Table 7 for details)
- ANSI/GBI 01-2010 – Green Building Assessment Protocol for Commercial Buildings (See Table 8 for details)

2.0 USES

Angelus Block concrete masonry units are used for load-bearing and nonload-bearing wall construction and also for masonry veneer applications.

3.0 DESCRIPTION

Angelus Block Concrete Masonry Units: Angelus Block concrete masonry units are manufactured in hollow and

solid, structural and nonstructural units with lightweight or normal-weight aggregates. The units are available in typical widths of 4, 6, 8, 10, 12 and 16 inches (102, 152, 203, 254, 304 and 406 mm) and typical heights are 4, 6 and 8 inches (102, 152 and 203 mm)].

The units contain the minimum type and percentage of recycled content, by weight, as set forth in Table 1.

4.0 CONDITIONS**4.1 Code Compliance:**

Evaluation of Angelus Block concrete masonry units for compliance with the requirements of the International Codes is outside the scope of this evaluation report. Evidence of code compliance must be submitted by the permit applicant to the Authority Having Jurisdiction (AHJ) for approval.

4.2 Green Rating Systems, Standards and Code Eligibility:

The information presented in Tables 2 through 8 of this report provides a matrix of areas of evaluation and corresponding limitations and/or additional project-specific requirements and offer benefit to individuals who are assessing eligibility for credits or points.

The final interpretation of the specific requirements of the respective green building rating system, standards and/or code rests with the developer of that specific rating system, standard or the AHJ, as applicable.

Decisions on compliance for those items noted as “Eligible for Points” in Tables 2 through 8 rests with the user of this report, and those items are subject to the conditions noted. The user is advised of the project specific provisions that may be contingent upon meeting specific conditions, and the verification of those conditions is outside the scope of this report. Rating systems or standards often provide supplemental information as guidance. Compliance for items noted as “Verified Attribute” are also subject to any conditions noted in the tables.

5.0 BASIS OF EVALUATION

The information in this report, including the “Verified Attribute”, is based upon the following supporting documentation:

- ICC-ES Evaluation EG101. [Evaluation applies to CALGreen Sections A.4.405.3 and A5.405.4; ICC 700 Section 604.1; LEED NC MR Credit 4; LEED Schools MR Credit 4; LEED CS MR Credit 4; LEED Homes MR Credit 2.2; ANSI/GBI Section 10.1.2.1].

6.0 IDENTIFICATION

Angelus Block concrete masonry units are identified on the delivery documentation with the manufacturer’s name (Angelus Block Company, Inc.), manufacturing plant

location (Orange, California; Fontana, California; Gardena, California; or Oxnard, California); the product identification (Angelus Block 25% recycled content); and the VAR number (VAR-1018).

TABLE 1—MINIMUM RECYCLED CONTENT BY WEIGHT SUMMARY

PRODUCT	% PRE-CONSUMER RECYCLED CONTENT	% POST-CONSUMER RECYCLED CONTENT	% MINIMUM RECYCLED CONTENT
Angelus Block concrete masonry units (all sizes)	0.0	25.0	25.0

TABLES 2 THROUGH 8

Section Number	Section Intent	Possible Points	Conditions Of Use To Qualify For Points	Finding
TABLE 2—SUMMARY OF AREA OF ELEGIBILITY WITH THE 2010 CALIFORNIA GREEN BUILDING STANDARDS CODE (CALGREEN)				
A4.405.3 A5.405.4	Recycled content	----	To achieve Tier 1 – Use materials, equivalent in performance to virgin materials, with a postconsumer or preconsumer recycled content value (RCV) for a minimum of 10% of the total value, based on estimated cost of materials on the project. To achieve Tier 2 – Use materials with a postconsumer or preconsumer RCV for a minimum of 15% of the total value, based on estimated cost of materials on the project. RCV shall be determined as follows: RCV = (% PC X material cost) + 0.5 (% PI X material cost) Notes: 1. PC means post consumer waste. 2. PI means post industrial waste.	●
TABLE 3—SUMMARY OF AREA OF ELEGIBILITY WITH THE NATIONAL GREEN BUILDING STANDARD (ICC 700-2008)				
604.1	Use two or more major and/or minor building materials containing recycled content	2 6 max	2, 4 or 6 points may be earned when products are used with another major building component with recycled content of 5% < 50%; 50% < 75%; ≥ 75%, respectively. Angelus Block qualifies for 2 points.	●
TABLE 4—SUMMARY OF AREA OF ELEGIBILITY WITH USGBC'S LEED 2009 FOR NEW CONSTRUCTION AND MAJOR RENOVATIONS				
MR 4	Recycled content	1 2 max	To earn 1 point use materials with recycled content such that the sum of postconsumer recycled content plus 1/2 of the preconsumer content constitutes at least 10%, based on cost, of the total value of the materials in the project. To earn 2 points use 20% or more.	●
TABLE 5—SUMMARY OF AREA OF ELEGIBILITY WITH USGBC'S LEED 2009 FOR SCHOOLS NEW CONSTRUCTION AND MAJOR RENOVATIONS				
MR 4	Recycled content	1 2 max	To earn 1 point use materials with recycled content such that the sum of postconsumer recycled content plus 1/2 of the preconsumer content constitutes at least 10%, based on cost, of the total value of the materials in the project. To earn 2 points use 20% or more.	●
TABLE 6—SUMMARY OF AREA OF ELEGIBILITY WITH USGBC'S LEED 2009 FOR CORE AND SHELL DEVELOPMENT				
MR 4	Recycled content	1 2 max	To earn 1 point use materials with recycled content such that the sum of postconsumer recycled content plus 1/2 of the preconsumer content constitutes at least 10%, based on cost, of the total value of the materials in the project. To earn 2 points use 20% or more.	●
TABLE 7—SUMMARY OF AREA OF ELEGIBILITY WITH USGBC'S LEED FOR HOMES 2008				
MR 2.2	Recycled content	0.5	To earn 0.5 point use masonry for exterior walls where the masonry with recycled content such that the sum of postconsumer recycled content plus 1/2 of the postindustrial (preconsumer) content constitutes a minimum total recycled content of 25%.	●
TABLE 8—SUMMARY OF AREA OF ELEGIBILITY WITH ANSI/GBI 01-2010 – GREEN BUILDING ASSESSMENT PROTOCOL FOR COMMERCIAL BUILDINGS				
10.1.2	Materials content - Assemblies	1 8 max	Recycled postconsumer or postindustrial (preconsumer) content materials accounted for 1% to 20% or more of building materials. Percentage is calculated as 100 x A (total cost or weight of recycled content materials) ÷ B (total cost or weight of all building materials).	●
●	= Verified attribute			