




10x4x16 Shotblast CMU




10x4x16 Standard




10x4x16 Bond Beam



10x4x16 Open End Standard



10x4x16 Open End Bond Beam



10x4x8 Half



10x4x8 U-Lintel

Degree of texturing of Shotblast units will vary from unit to unit.

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:

 11374 Tuxford St.
 Orange, CA

 Sun Valley, CA 91352
 Fontana, CA

 (818) 767-8576
 Gardena, CA

Oxnard, CA Indio, CA Bakersfield, CA

www.AngelusBlock.com

info@AngelusBlock.com

Features

When used as a field, the course module of 4-inch high cmu creates a more traditional scale, expressing the warmth of historical masonry. 4-high units are also effective as banding elements to add sightlines and interest to large elevations. The Shotblast texture roughens the surface and removes sharp edges.

Availability

Special order. Shotblast on multiple sides is available. Units can be made in any of our integral color options.

Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

Sustainable Features

- This product is included in Type III Environmental Product
 Declarations for Angelus Block Concrete Masonry Units, specific
 to location and mix designs, and in one of six Health Product
 Declarations, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.



This is a low impact CarbonKind™ product which substantially reduces CO₂e. Learn more at Angelus Block/CarbonKind.