

10x8x16 Precision CMU





10x8x16 Open End Bond Beam









10x8x16 With 8-inch Off-Set Core Special Order

Availability

Basic configurations may be limited in inventory. Special order as noted. Units may be made in any of our integral color options on special order.

Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

Sustainable Features

- This product is included in Type III Environmental Product Declarations for Angelus Block Concrete Masonry Units, specific to location and mix designs, and in one of six Health Product Declarations, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.

Cells and web configurations as shown are representational only, and actual configurations may differ.

Orange, CA

Fontana, CA

Gardena, CA

Corporate Office & Plants: 11374 Tuxford St. Sun Valley, CA 91352 (818) 767-8576

www.AngelusBlock.com

info@AngelusBlock.com

Oxnard, CA

Bakersfield, CA

Indio, CA



This is a low impact CarbonKind[™] product which substantially reduces CO₂e. Learn more at Angelus Block/CarbonKind.

