


# 4-Score 2x1 Burnished


## **CONCRETE MASONRY UNITS**



8x8x16 4-Score 2x1

12x8x16
4-Score 2x1
May be limited in plant location.

4-Score 2x1 Running Bond



Aggregate exposure in all Burnished units will vary across the unit face, and from unit to unit.

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:

11374 Tuxford St.Orange, CAOxnard, CASun Valley, CA 91352Fontana, CAIndio, CA(818) 767-8576Gardena, CABakersfield, CA

www.AngelusBlock.com

info@AngelusBlock.com

#### **Features**

Equally spaced projections and 1-inch deep scores create a ribbed effect. Burnishing reveals the aggregate matrix on just the projected faces for a rich, natural, yet refined look.

Add relief and depth of texture to fields and bands; create visual anchoring to lower elevations or striking accent to top of walls.

## **Availability**

**Special order only.** Configurations such open ends and open end bond beams may be available. Units can be made in any of our integral colors.

### **Standards**

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

## Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

## **Sustainable Features**

- This product is included in Type III Environmental Product
   Declarations for Angelus Block Concrete Masonry Units, specific
   to location and mix designs, and in one of six Health Product
   Declarations, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.



This is a low impact CarbonKind™ product which substantially reduces CO<sub>2</sub>e. Learn more at Angelus Block/CarbonKind.