



9-Score Shotblast CMU



8x8x16 9-Score Special order.

9-Score Running Bond



 $\label{thm:local_problem} \mbox{Aggregate exposure in all Burnished units will vary across the unit face, and from unit to unit.}$

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:

11374 Tuxford St.Orange, CAOxnard, CASun Valley, CA 91352Fontana, CAIndio, CA(818) 767-8576Gardena, CABakersfield, CA

www.AngelusBlock.com

info@AngelusBlock.com

Features

Nine vertical scores, 3/8-in wide and deep, simulate raked joints. The effect is a tight grid that can effectively add accent or interest to the elevation.

The Shotblast texture roughens the surface and removes sharp edges.

Availability

Special order only. Shotblasting of multiple sides is available. Configurations such as open ends and open end bond beams may be available. May be limited in plant location. Units can be made in any of our integral color options.

Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

Sustainable Features

- This product is included in Type III Environmental Product
 Declarations for Angelus Block Concrete Masonry Units, specific
 to location and mix designs, and in one of six Health Product
 Declarations, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.



This is a low impact CarbonKind™ product which substantially reduces CO₂e. Learn more at Angelus Block/CarbonKind.