


Castle Rock Offset Split Face CMU

CONCRETE MASONRY UNITS




8x8x16 Castle Rock

Unit A of two-unit package.




8x8x16 Castle Rock

Unit B of two-unit package.




10x8x16 Castle Rock

Unit A of two-unit package.




10x8x16 Castle Rock

Unit B of two-unit package.



12x8x16 Castle Rock


Unit A of two-unit package.



12x8x16 Castle Rock

Unit B of two-unit package.







*Depth varies with split.

Variation in aggregate exposure is inherent in all split face products.

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:

 11374 Tuxford St.
 Oran

 Sun Valley, CA 91352
 Fonta

 (818) 767-8576
 Gard

Orange, CA Fontana, CA Gardena, CA Oxnard, CA Indio, CA Bakersfield, CA

www.AngelusBlock.com

info@AngelusBlock.com

Features

Castle Rock creates a textured, random appearance with depth and shadowing that provides character and warmth to building elevations.

Availability

Special order only. This product may be limited in plant location. Corner units are available for 8-inch and 10-inch wide units. Castle Rock is available in any of our integral color options.

Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

Sustainable Features

- This product is included in Type III Environmental Product
 Declarations for Angelus Block Concrete Masonry Units, specific
 to location and mix designs, and in one of six Health Product
 Declarations, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.



This is a low impact CarbonKind™ product which substantially reduces CO₂e. Learn more at Angelus Block/CarbonKind.