



Half-Face Split CMU


CONCRETE MASONRY UNITS




8x8x16 Standard Mid-Split




Mid-Split 1-Side 1-End




Mid-Split Running Bond



Mid-Split Stack Bond



Mid-Split Running Bond Texture Break Without Joint



Variation in aggregate exposure is inherent in all split face products.

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:

11374 Tuxford St. Orange, CA Oxnard, CA
Sun Valley, CA 91352 Fontana, CA Indio, CA
(818) 767-8576 Gardena. CA Bakersfield. CA

www.AngelusBlock.com

info@AngelusBlock.com

Features

With just half the face in a split texture, Mid-Split CMU provide design effects without projections. Used as a field, a running bond installation creates a checkerboard pattern; in stack bond, vertical striations. Inserted in a field of typical precision or split face units, the Mid-Split can add accents at random, or in phasing patterns. This unit can also facilitate clean inside corners for split textured walls.

Availability

Special order only. Configurations such as open ends and open end bond beams may be available. Units may be made in any of our integral color options.

Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units

Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

Sustainable Features

- This product is included in Type III Environmental Product
 Declarations for Angelus Block Concrete Masonry Units, specific
 to location and mix designs, and in one of six Health Product
 Declarations, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.



This is a low impact CarbonKind™ product which substantially reduces CO₂e. Learn more at Angelus Block/CarbonKind.