



# Hi-Lite Mark II


CONCRETE MASONRY UNITS



**6x8x16**  
**Hi-Lite Mark II**




**8x8x16**  
**Hi-Lite Mark II**



**12x8x16**  
**Hi-Lite Mark II**

Hi-Lite Mark II  
Running Bond



## Features

With two angular projections, the Hi-Lite Mark II offers strong relief and shadow patterns that change with the angle of sunlight.

Popouts, angles, and overhangs enliven walls with contrasts of highlights and shade. Use them as individual units for accent, or in fields for pattern and texture.

## Availability

**Special order only.** Configurations such as open ends and open end bond beams may be available. This item may be limited in plant location. Units may be made in any of our integral color options.

## Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

## Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

## Sustainable Features

- This product is included in Type III Environmental Product Declarations for Angelus Block Concrete Masonry Units, specific to location and mix designs, and in one of six *Health Product Declarations*, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See *Sustainable Design & Angelus Block Products* for detailed information. A copy is available from your representative, or as a download at [www.AngelusBlock.com](http://www.AngelusBlock.com).

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:  
11374 Tuxford St.  
Sun Valley, CA 91352  
(818) 767-8576

Orange, CA  
Fontana, CA  
Gardena, CA

Oxnard, CA  
Indio, CA  
Bakersfield, CA

[www.AngelusBlock.com](http://www.AngelusBlock.com)

[info@AngelusBlock.com](mailto:info@AngelusBlock.com)



This is a low impact CarbonKind™ product which substantially reduces CO<sub>2</sub>e. Learn more at Angelus Block/CarbonKind.



**WARNING:** This product can expose you to Silica, crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

©2021 Angelus Block Co., Inc.