



# **Veneer / Composite CMU**

# **Combed Face**



3x8x16 Solid

### Combed Face Running Bond



#### **Features**

The Combed texture has slight vertical striations that provide a "brushed" surface

These units are suitable for use in anchored veneer or composite masonry applications.

For veneer masonry: Use in anchored veneer applications per TMS 402 Chapter 12 and TMS 602.

For composite masonry: Use in multiwythe masonry per CBC and TMS 402 and TMS 602.

## **Availability**

Special order only. Available in any of our integral color options.

#### **Standards**

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

#### **Sustainable Features**

- This product is included in Type III Environmental Product
  Declarations for Angelus Block Concrete Masonry Units, specific
  to location and mix designs, and in one of six Health Product
  Declarations, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.

Corporate Office & Plants: 11374 Tuxford St. Sun Valley, CA 91352 (818) 767-8576

Orange, CA Fontana, CA Gardena, CA Oxnard, CA Indio, CA Bakersfield, CA

www.AngelusBlock.com

info@AngelusBlock.com



This is a low impact CarbonKind™ product which substantially reduces CO<sub>2</sub>e. Learn more at Angelus Block/CarbonKind.