



E-Z MIX INC.

DECK MUD

PRODUCT

PMP Deck Mud

DESCRIPTION

PMP Deck Mud is a dry, factory blended mortar specifically designed for use by tile and masonry contractors. The product is a preblended mix of washed plaster sand and Type II/V cement. Pre-blending allows the cement to thoroughly coat the sand particles thus producing a stronger than jobsite mix. The mortar bed is compatible with cement based and most water based latex adhesives. Standard mix design is 4:1 by weight. **Special mix designs available.**



USES

PMP Deck Mud is a leveling mortar underlayment for all types of pavers, tile and marble on floors and countertops. It can be used as a **Mortar for Rock Blanket** when mixed design is 2 to 1 sand to cement ratio by volume.

ADVANTAGES

- Factory pre-blended for highest quality
- Excellent for multi-story and difficult access jobs
- Quality control – a consistent batch every time
- No sand piles or wasted material

PACKAGING

Available in 75 lb. paper bags, 3000 lb. bulk bags and bulk. Information on silo and bulk systems available upon request.

COVERAGE

One 75 lb. bag will yield approximately 9.6 square feet at 1 inch thickness.

TECHNICAL DATA

PMP Deck Mud conforms to the volume composition for floor applications of ANSI A108.1A 2.2., IBC and CBC Table 2103.11, CBC Table 2103A.11, **Caltrans Standard Specification 2018 Sec. 20-5.03(B)(2)(d) and 51-1.02F** and L.A City approval RRR24968.

APPLICATIONS

Mix PMP Deck Mud with only enough clean, potable water to allow placing and packing. You should be able to form a ball when compacted in your hands. Compact and screed into place. Allow for proper cure prior to application of any adhesives. Do not try to accelerate cure with fans. Bonding mortar should be tested for suitability with PMP Deck Mud. Do not use epoxy mortars without the manufacturer cure time and compatibility concerns.

LIMITATIONS

- Do not apply when temperature is below or may fall below 40°F prior to curing
- Do not overwater or overmix
- Do not accelerate curing time with fans
- Consult manufacturer prior to using epoxy bonding mortars.

WARRANTY

The technical information and usage statement are based on our best knowledge. The content of this specification sheet is presented for information purposes only and do not constitute responsibility for their use. The manufacturer will replace only that material which is proven defective due to quality of the components of the manufacturing process.

CAUTION

Prolonged exposure to dust may cause delayed lung disease. Eliminate exposure to dust. Use NIOSH approved mask for silica dust. Freshly mixed material may cause skin irritation. Avoid direct contact when possible and wash exposed skin areas promptly with water and get prompt medical attention. See Safety Data Sheet.

For technical support contact:

www.ezmixinc.com jjara@ezmixinc.com

Corporate Office:
11374 Tuxford St.
Sun Valley, CA 91352
(818) 767-8576

Sun Valley Plant:
11450 Tuxford St.
Sun Valley, CA 91352
(818) 768-0568

Rialto Plant:
3355 Industrial Drive.
Rialto, CA 92316
(909) 874-7686



WARNING: This product can expose you to chemicals including Chromium (hexavalent compounds), which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.